


## SODIUM HYPOCHLORITE.


An aggressive oxidizer that presents a major storage challenge.



Commonly known as bleach, sodium hypochlorite is used in a variety of applications, particularly for the disinfection of drinking water and wastewater. When it comes to storage of this chemical, three factors must be considered:

- UV can degrade sodium hypochlorite, so special precautions must be taken to reduce this effect.
- Sodium hypochlorite typically contains transition metals such as nickel, iron and copper, which can buildup in a storage tank creating off-gassing.
- “Hypo” is a potent oxidizer, so all materials in the chemical’s storage tank must be up to the task.

By addressing all three of these issues, this caustic chemical can be contained in a more secure and effective manner, with a tank system that meets NSF/ANSI Standard 61 for chemical storage.





**NaOCl**  
SODIUM HYPOCHLORITE

## The Poly Processing Hypo System

Poly Processing's Sodium Hypochlorite Storage Systems are specifically designed for containment of this challenging chemical. By using carbon black, white or gray compound XLPE resin, **UV degradation of the chemical can be dramatically reduced.** Mastic coatings and insulation are other ways to reduce UV's effect on the chemical.

To **prevent the potential buildup of transition metals in the tank**, Poly has developed the IMFO® system. This special design allows for full drainage of the tank, which can greatly increase the half-life of the chemical\*.

\* Natural tanks are available for indoor use.

Poly's OR-1000™ system is another key component of the Hypo System. OR-1000™ is the result of our exclusive rotomolding process, which creates a seamless bond between an inner surface of medium-density polyethylene and an outer surface of high-density crosslinked polyethylene. OR-1000™ allows **four times the antioxidant strength** of a normal polyethylene. In any application where OR-1000™ is used, all wetted surfaces - including covering the face of the IMFO® drain - are completely covered by the material, eliminating any opportunity for a chemical attack on the structural portion of the tank.

CHEMICAL	RESIN TYPE	SPECIFIC GRAVITY RATING	FITTING MATERIAL	GASKET MATERIAL	BOLT MATERIAL
Sodium Hypochlorite 2%–15%	XLPE with OR-1000™	1.9	PVC	EPDM/Viton®	Titanium
Sodium Hypochlorite < 2%	XLPE	1.35–1.9	PVC	EPDM/Viton®	Titanium

» See our website for a complete Chemical Resistance Chart.

**NOTE:** To meet NSF-61 certification, use EPDM or Viton® GF.

## Tank Specifications




- **High-density crosslinked polyethylene (XLPE)** outer surface ensures maximum corrosion protection through molecular bonding.
- **OR-1000™** molecularly bonds XLPE with an antioxidant inner surface that resists the heavily oxidizing nature of sodium hypochlorite.
- **Integrally Molded Flanged Outlet (IMFO®)** constructed as part of tank ensures complete drainage. Non-IMFO® options also available
- **UV protection** for the chemical is achieved by using compounded black, white or gray resin or insulation coating to help maximize the half-life of the chemical for outdoor applications.

## Recommended System Components



**Secondary containment:**  
Recommended.  
**Alternative:** PPC secondary containment basin of XLPE, or SAFE-Tank® if concrete containment is not available.



**Fittings:**  
IMFO® to prevent transition metal buildup

**NOTE:** Do NOT use stainless steel or Alloy C-276 due to nickel content reaction.



**Plumbing:**  
Requires flexible, Hypo-resistant connections [see pages 54-55] to allow for lateral and vertical tank contraction and expansion, and to reduce vibration stress



**Venting:**  
SAFE-Surge® manway cover is recommended on pneumatically loaded systems to support tank longevity.

The above components are just a few of the many options offered by Poly Processing. See our website or talk to your Poly Processing representative to find out more.



**CAUTION!** The life of a Sodium Hypochlorite Storage System is greatly affected by the quality of the chemical itself. Tank owners are cautioned to use high-quality sodium hypo with low iron, nickel and copper content, to avoid decomposition of the chemical and acceleration of the oxidization and degradation of the tank.

## TECHNICAL OVERVIEW: Sodium Hypochlorite Storage Tanks.

### TANK

#### IMFO® Vertical Flat Bottom of XLPE with OR-1000™:

- 1,000–13,650 gallons
- 1.9 spg rating

NOTE: 230–1,000 gallons do not require OR-1000™.

#### Non-IMFO® alternative\*:

##### Standard Vertical Flat Bottom XLPE with OR-1000™:

- 1,000–13,650 gallons
- 1.9 spg rating

NOTE: 30–1,000 gallons do not require OR-1000™.

\*Three-year warranty offered on Non-IMFO® alternatives.

##### SAFE-Tank® XLPE:

- 1,500–8,700 gallons
- 1.9 spg rating for primary tank with OR-1000™
- Spg ratings for secondary tanks  $\geq$  3,000 gallons may be equal to or 1 less spg than primary tank.
- All other tank sizes must equal primary tank spg rating.

NOTE: 55–1,000 gallons do not require OR-1000™.

Black, white or gray color or insulation with mastic coating required in outdoor applications to minimize bleach degradation and maximize chemical half-life.

### SECONDARY CONTAINMENT

Recommend **SAFE-Tank®** secondary XLPE as shown above.

#### Non-SAFE-Tank® Alternatives:

- PPC secondary containment basin
- Other secondary containment suitable for sodium hypochlorite, of adequate size for use

### FITTINGS

**Sidewall:** Recommend 3" maximum B.O.S.S.® fitting

**Dome:** No restrictions

### PLUMBING TO THE TANK

- Required use of **flexible connections** with fittings on lower third of sidewall
  - » Allows for lateral and vertical expansion and contraction of the tank
  - » Reduces pump and piping vibration stress on the tank
- Expansion joints must meet the following minimum requirements:
  - » Axial Compression  $\geq$  1.5"
  - » Axial Extension  $\geq$  0.625"
  - » Lateral Deflection  $\geq$  0.750"
  - » Angular Deflection  $\geq$  14°
  - » Torsional Rotation  $\geq$  4°

### VENTING

Please refer to the venting chart on [www.polyprocessing.com/pdf/technical/Venting.pdf](http://www.polyprocessing.com/pdf/technical/Venting.pdf)

### FOUNDATION AND RESTRAINTS

- PPC IMFO® tank pad or smooth concrete, asphalt or steel foundation designed to accommodate IMFO®, SAFE-Tank® or vertical tank
- No restraint or ladder attachment bands circumscribing the tank are allowed. Cable restraint systems must pass cables over the top of the tank.

### TEMPERATURE

Product should not exceed 100°F at delivery or during storage to reduce the decomposition of the chemical and maintain ASTM D1998 design parameters.

### LID

SAFE-Surge® manway cover for pneumatically loaded tanks; bolted manway cover for all other applications

### OPTIONS

Restraint systems for wind and seismic, level gauges, ladders, heating pads, insulation, fume-tight manway cover, NSF-61 certification and engineering stamp

#### CALIFORNIA

8055 S. Ash St.  
French Camp, CA 95231  
Tel: 877.325.3142

#### LOUISIANA

P. O. Box 4150  
2201 Old Sterlington Rd.  
Monroe, LA 71203  
Tel: 866.590.6845

#### VIRGINIA

161 McGhee Rd.  
Winchester, VA 22603  
Tel: 866.590.6845

[sales@polyprocessing.com](mailto:sales@polyprocessing.com)